


66507 130E460

Figure 1



66601 1500330




Figure 2

server




Figure 4




Figure 5





Figure 6

600

Class Hierarchy

```
class java.lang.Object
interface com.ibm.jtc.ApplicationMediator (extends com.ibm.jtc.JTC)
class com.ibm.jtc.ApplicationMediatorImpl (implements com.ibm.jtc.ApplicationMediator,
com.ibm.jtc.ViewListener, com.ibm.jtc.RequestResponseListener)
interface com.ibm.jtc.Destination (extends com.ibm.jtc.JTC)
class com.ibm.jtc.DestinationImpl (implements com.ibm.jtc.Destination)
class java.util.EventObject (implements java.io.Serializable)
class com.ibm.jtc.PlacementEvent (implements java.io.Serializable)
class com.ibm.jtc.RequestEvent (implements java.io.Serializable)
class com.ibm.jtc.TopEvent (implements java.io.Serializable)
class com.ibm.jtc.ViewEvent (implements java.io.Serializable)
class com.ibm.jtc.Factory (implements java.io.Serializable)
interface com.ibm.jtc.JTC (extends java.io.Serializable)
interface com.ibm.jtc.PlacementListener
interface com.ibm.jtc.RequestListener
interface com.ibm.jtc.RequestResponseListener
class java.lang.Throwable (implements java.io.Serializable)
class java.lang.Exception
class com.ibm.jtc.RequestException (implements java.io.Serializable)
class com.ibm.jtc.ValidationRuleException (implements java.io.Serializable)
interface com.ibm.jtc.TopListener
class com.ibm.jtc.Transporter (implements com.ibm.jtc.RequestListener, com.ibm.jtc.JTC)
class com.ibm.jtc.ValidationRule (implements java.io.Serializable)
interface com.ibm.jtc.ViewController (extends com.ibm.jtc.JTC)
interface com.ibm.jtc.ViewListener
```

Figure 7



ViewController

FIGURE 8A

Variables

800

Name	Declaration	Description
copyright	public static final String copyright	(c) International Business Machines, Inc., 1997 1998 1999. All rights reserved.

FIGURE 8B

802

Methods

Name	Declaration	Description
addViewListener	public abstract void addViewListener (ViewListener listener)	Invoked when a ViewListener is added.
getComponent	public abstract Component getComponent ()	Invoked when the ViewController as a component is needed.
getPermissions	public abstract String[] getPermissions ()	Invoked when the ViewController permission keys are needed.
isValid	public abstract boolean isValid ()	Invoked when a ViewController's GUI state needs to be checked to see if it is valid.
isVisible	public abstract boolean isVisible ()	Invoked to see if the ViewController is visible.
refresh	public abstract void refresh (Object data)	Invoked to supply new or changed data.
removeViewListener	public abstract void removeViewListener (ViewListener listener)	Invoked to remove a ViewListener.
setPermissions	public abstract void setPermissions (Hashtable permissions)	Invoked to set the permissions keys and values.
set Properties	public abstract void setProperties (Properties properties)	Invoked to set the properties
setResources	public abstract void setResources (ResourceBundle bundle)	Invoked to set the resources.
setValidationLevel	public abstract void setValidationLevel (int level)	Invoked to give a hint to the ViewController as to what validation level to use. The value for level defined in this interface include: NONE = try to do no validation EVENT = try to do validation every event (key) FOCUS = try to do validation on focus change VIEWEVENT = try to do validation before a ViewEvent is issued.
setVisible	public abstract void setVisible (boolean visible)	Invoked to set the visibility.

Figure 9A

ViewControllerImpl

Variables 900

Name	Declaration	Description
copyright	public static final String copyright	(c) International Business Machines Inc., 1997 1998 1999. All rights reserved.
validationLevel	protected int validationLevel	The current validation level
viewEvent	protected ViewEvent viewEvent	A reference to a ViewEvent. Create one ViewEvent reuse it between events.
data	protected Object data	An reference to the data.

Figure 9B

Constructors 902

Name	Declaration	Description
ViewControllerImpl	public ViewControllerImpl()	Default constructor.

Figure 9C

904

ViewControllerImpl

Methods

Name	Declaration	Description
addViewListener	public final void addViewListener(ViewListener listener)	Add a ViewListener
clear	public void clear()	Clear local state by setting the data reference to null and by removing all ViewListeners.
exit	public void exit()	Get ready to exit. Clear local state by setting the data reference to null, removing all ViewListeners and setting view listeners to null.
fireViewEvent	public final void fireViewEvent(ViewEvent event)	If the ViewEvent is not null then send it to all ViewListeners.
getComponent	public Component getComponent()	Return the Component that is "this" ViewController. By default, "this" is returned. Redefine this method in ViewControllerBaseImpl when you have a non-java.awt.Component subclass.
getJTCs	public Vector getJTCs()	Return all JTC type objects defined. By default null is returned. Typically, ViewControllers will not return anything.
getPermissions	public String[] getPermissions()	For example, consider the common case of operator override. In a grocery store, if a cashier makes a mistake, a manager inserts a key or enters a password to enable more function on the cash register. The software analogy is that a button may become active or disabled. Suppose the ViewController implements a button labeled "Override" and it is the only component whose state can be visibly altered outside the ViewController. The ViewController writer will return "Override" respectively. A management system that maintains user privileges is queried at runtime. The ViewController is then called with setPermissions(keys, values) where keys is "Override" and values is "0x001". The ViewController writer now responds to this request by turning off the button. Instead of hard coding the possible roles, the ViewController simply reacts to key/value settings. By default, nothing is returned.
init	public void init()	Initialize, by default do nothing.
isEnabled	public boolean isEnabled()	Is this ViewController enabled?
isValid	public boolean isValid()	Is the ViewController in a consistent state? This usually means: Do all fields pass ValidationRules? The meaning could also be application specific. This value can provide other components with the ability to show a visual indicator, such as an X or a check in a tree menu indicating incomplete or partial data. The default value is true.
isVisible	public boolean isVisible()	Is this ViewController visible?
refresh	public void refresh(Object data)	Data objects are being passed in. By default, keep a reference to them. Interpretation of the data is performed in the subclass. For example, suppose the data being passed is a Customer object. Then a subclass can perform the following: This can be extended to more complex data types and data type composites (i.e. arrays, Vectors, etc.).
removeViewListener	public final void removeViewListener(ViewListener listener)	Remove a ViewListener
setEnabled	public void setEnabled(boolean toggle)	Enable or disable the ViewController. Remember the state and ask the ViewControllerBaseImpl to handle it.
setPermissions	public void setPermissions(Hashtable permissions)	Given a set of keys and values, update the internal state of the ViewController. The keys and values are supplied via a management system and reduce to roles (i.e. users and groups). The possible values in the key/value pairs are application and ViewController specific. For example, create an interface to define the keys and values: <pre> public interface Customer { public static final String DETAILS = "DETAILS"; public static final String ON = "1"; public static final String OFF = "0"; } </pre> then set the ViewController: <pre> Hashtable permissions = new Hashtable(); permissions.put(Customer.DETAILS, Customer.ON); viewController.setPermissions(permissions); </pre> The ViewController will interpret the meaning of ON and perform the necessary action, such as active a button. The meaning of keys, values and actions should be defined in GUI apps. By default, nothing is returned.
setProperties	public void setProperties(Properties properties)	Set the properties. Default is to do nothing.
setResources	public void setResources(ResourceBundle bundle)	Set the ResourceBundles. Default is to do nothing.
setValidationLevel	public void setValidationLevel(int level)	Set the validation level to indicate when ValidationRules should be applied. Four constants are defined in the ValidationRule class: NONE COMPONENT FOCUS VIEWEVENT
setVisible	public void setVisible(boolean visible)	This value will be stored for the subclass to reference and act. The default value is ValidationRule.NONE.
toString	public String toString()	Set the ViewController's visibility on or off. Remember the state and ask the ViewControllerBaseImpl to handle it. Return the instance class name

Figure 10A

viewControllerBaseImpl

Variables

Name	Declaration	Description
copyright	public static final String copyright	(c) International Business Machines Inc., 1997 1998 1999. All rights reserved.

Figure 10B

Constructors

Name	Declaration	Description
viewControllerBaseImpl	public viewControllerBaseImpl()	Default constructor.

Figure 10C

Methods

Name	Declaration	Description
getComponent	public Component getComponent()	By default, return <i>this</i> . This works when the superclass is derived from java.awt.Component. Otherwise, override this method and return your own <i>this</i> , but be sure to override setEnabled and setVisible also.
setEnabled	public void setEnabled(boolean toggle)	By default, passes the call to the super class.
setVisible	public void setVisible(boolean visible)	By default, passes the call to the super class.

Figure 11A

ViewControllerAdapter

Variables	
Name	Declaration
copyright	public static final String copyright
	(c) International Business Machines Inc., 1997 1998 1999. All rights reserved.

Figure 11B

Constructors	
Name	Declaration
ViewControllerAdapter	public ViewControllerAdapter()
	Constructor.

Figure 11C

Methods	
Name	Declaration
actionPerformed	public void actionPerformed(ActionEvent e)
adjustmentValueChanged	public void adjustmentValueChanged(AdjustmentEvent e)
componentAdded	public void componentAdded(ContainerEvent e)
componentHidden	public void componentHidden(ComponentEvent e)
componentMoved	public void componentMoved(ComponentEvent e)
componentRemoved	public void componentRemoved(ContainerEvent e)
componentResized	public void componentResized(ComponentEvent e)
componentShown	public void componentShown(ComponentEvent e)
focusGained	public void focusGained(FocusEvent e)
focusLost	public void focusLost(FocusEvent e)
itemStateChanged	public void itemStateChanged(ItemEvent e)
keyPressed	public void keyPressed(KeyEvent e)
keyReleased	public void keyReleased(KeyEvent e)
keyTyped	public void keyTyped(KeyEvent e)
mouseClicked	public void mouseClicked(MouseEvent e)
mouseDragged	public void mouseDragged(MouseEvent e)
mouseEntered	public void mouseEntered(MouseEvent e)
mouseExited	public void mouseExited(MouseEvent e)
mouseMoved	public void mouseMoved(MouseEvent e)
mousePressed	public void mousePressed(MouseEvent e)
mouseReleased	public void mouseReleased(MouseEvent e)
textValueChanged	public void textValueChanged(TextEvent e)

Figure 12D

```

/**
 * Given a list of class names, apply each validation rule of the classes
 * to input string and return the formatted result.
 *
 * @return the viewable formatted string.
 * @param classNames a comma-separated fully qualified list of concrete AbstractRule classes.
 * @param input the input string to apply edit rules to.
 * @exception ValidationRuleException if there was an error in applying the edits.
 */
public static String applyEdits(String classNames, String input) throws ValidationRuleException {
    int commaIndex = -1;
    int curIndex = 0;
    do {
        commaIndex = classNames.indexOf(',', curIndex);
        if (commaIndex == -1) {
            commaIndex = classNames.length();
        }
        String className = classNames.substring(curIndex, commaIndex).trim();
        try {
            ValidationRule rule = (ValidationRule) Factory.newInstance(className);
            input = rule.edit(input);
        } catch (ValidationRuleException re) {
            throw re;
        } catch (Exception e) {
            throw new ValidationRuleException("Rule class '" + className + "' not found.");
        }
        curIndex = commaIndex + 1;
    } while (curIndex < classNames.length());
    return input;
}

```

Figure 13A

ValidationRuleException

Variables		
Name	Declaration	Description
copyright	public static final String copyright	(c) International Business Machines Inc., 1997 1998 1999. All rights reserved.

Figure 13B

Constructors		
Name	Declaration	Description
ValidationRuleException	public ValidationRuleException()	Default constructor.
ValidationRuleException	public ValidationRuleException(String s)	Constructor with a message to the rule exception.

Figure 14A

ViewEvent

1400

Variables

Name	Declaration	Description
_copyright	public static final String _copyright	(c) International Business Machines Inc., 1997 1998 1999. All rights reserved.
VIEWEVENT_FIRST	public static final int VIEWEVENT_FIRST	
OK	public static final int OK	
DONE	public static final int DONE	
OPEN	public static final int OPEN	
CLOSE	public static final int CLOSE	
CANCEL	public static final int CANCEL	
EXIT	public static final int EXIT	
FILE	public static final int FILE	
SAVE	public static final int SAVE	
SAVEAS	public static final int SAVEAS	
ERROR	public static final int ERROR	
WARNING	public static final int WARNING	
RETURN	public static final int RETURN	
LOAD	public static final int LOAD	
NOTIFY	public static final int NOTIFY	
NOTIFY2	public static final int NOTIFY2	
INFO	public static final int INFO	
SETUP	public static final int SETUP	
PRINT	public static final int PRINT	

Figure 14B

ViewEvent
(continued)

1400

Variables

Name	Declaration	Description
TITLEMESSAGE	public static final int TITLEMESSAGE	
STATUSMESSAGE	public static final int STATUSMESSAGE	
ERRORMESSAGE	public static final int ERRORMESSAGE	
SUGGESTIONMESSAGE	public static final int SUGGESTIONMESSAGE	
NEXT	public static final int NEXT	
PREVIOUS	public static final int PREVIOUS	
FIRST	public static final int FIRST	
LAST	public static final int LAST	
START	public static final int START	
BEGIN	public static final int BEGIN	
END	public static final int END	
PAUSE	public static final int PAUSE	
STOP	public static final int STOP	
RESTART	public static final int RESTART	
SUBMIT	public static final int SUBMIT	
BACKSPACE	public static final int BACKSPACE	
INSERT	public static final int INSERT	

Figure 14C

ViewEvent
(continued)

1400

Variables			Description
Name	Declaration		
HOME	public static final int HOME		
PGUP	public static final int PGUP		
PGDN	public static final int PGDN		
LEFT	public static final int LEFT		
RIGHT	public static final int RIGHT		
UP	public static final int UP		
DOWN	public static final int DOWN		
LIST	public static final int LIST		
MORE	public static final int MORE		
ADD	public static final int ADD		
DELETE	public static final int DELETE		
MODIFY	public static final int MODIFY		
NEW	public static final int NEW		
EDIT	public static final int EDIT		
COPY	public static final int COPY		
CUT	public static final int CUT		
PASTE	public static final int PASTE		
UNDO	public static final int UNDO		
REMOVE	public static final int REMOVE		
PLUS	public static final int PLUS		
MINUS	public static final int MINUS		
INCREMENT	public static final int INCREMENT		
DECREMENT	public static final int DECREMENT		
CHANGED	public static final int CHANGED		

Figure 14D

ViewEvent
(continued)

1400

Variables

Name	Declaration	Description
FILL	public static final int FILL	
EMPTY	public static final int EMPTY	
READY	public static final int READY	
VIEW	public static final int VIEW	
DETAILS	public static final int DETAILS	
READ	public static final int READ	
WRITE	public static final int WRITE	
SEARCH	public static final int SEARCH	
FIND	public static final int FIND	
HELP	public static final int HELP	
HINT	public static final int HINT	
TRAIN	public static final int TRAIN	
TEACH	public static final int TEACH	
SUGGEST	public static final int SUGGEST	
VIEWEVENTTEST1	public static final int VIEWEVENTTEST1	
VIEWEVENTTEST2	public static final int VIEWEVENTTEST2	
VIEWEVENTTEST3	public static final int VIEWEVENTTEST3	
VIEWEVENT LAST	public static final int VIEWEVENT LAST	
consumed	protected boolean consumed	Is event still valid
timestamp	protected long timestamp	Time stamp when event is fired.
data	protected Object data	Data reference

Figure 14E

1402

Constructors

Name	Declaration	Description
ViewEvent	public ViewEvent()	Constructs a ViewEvent
ViewEvent	public ViewEvent(Object source)	Constructs a ViewEvent
ViewEvent	public ViewEvent(Object source, int major)	Constructs a ViewEvent object with the specified source object and code;
ViewEvent	public ViewEvent(Object source, int major, int minor, Object data)	Constructs a ViewEvent object with the specified source object and code;
ViewEvent	public ViewEvent(Object source, int major, Object data)	Constructs a ViewEvent object with the specified source object and code;

Figure 14F

ViewEvent
(continued)

1404

Methods			
Name	Declaration	Description	
consume	public final void consume()	Consume this event.	
getData	public Object getData()	Return the data	
getMajor	public final int getMajor()	Return the major event code	
getMinor	public final int getMinor()	Return the event option	
getSource	public final Object getSource()	Gets the event source Overrides: <u>getSource</u> in class EventObject	
getTimestamp	public long getTimestamp()	Get the timestamp when the event was fired. By default, this was set by JTC.	
isConsumed	public final boolean isConsumed()	Is the event consumed?	
setConsumed	public final void setConsumed(boolean consumed)	Turn event consumed on/off.	
setData	public void setData(Object data)	Sets the data	
setMajor	public final void setMajor(int code)	Sets the event code	
setMinor	public final void setMinor(int code)	Sets the event option	
setSource	public final void setSource(Object source)	Sets the event source	
setTimestamp	public void setTimestamp(long time)	Set the timestamp when the event is fired. By default, this is set by JTC.	
toString	public String toString()	Returns a string representation of the object. The class of the event and the reason for the event is returned.	

Figure 15A

ViewListener
1500

Variables

Name	Declaration	Description
_copyright	public static final String _copyright	(c) International Business Machines Inc., 1997 1998 1999. All rights reserved.

Figure 15B

1502

Methods

Name	Declaration	Description
viewEventPerformed	public abstract void viewEventPerformed(ViewEvent event)	Invoked when a ViewEvent has been fired.

Name	Declaration	Description
copyright	public static final String _copyright	(c) International Business Machines, Inc., 1997 1998 1999. All rights reserved.

Methods

Name	Declaration	Description
addPlacementListener	public abstract void addPlacementListener (PlacementListener listener)	Invoked when a PlacementListener is added.
addRequestListener	public abstract void addRequestListener (RequestListener listener)	
addTopListener	public final void addTopListener (TopListener listener)	Add a TopListener.
addViewListener	public abstract void addViewListener (ViewListener listener)	Invoked when a ViewListener is added.
getPermissions	public abstract String[] getPermissions()	Invoked when the ApplicationMediator permission keys are needed.
init	public abstract void init (ApplicationMediator applicationMediator)	Invoked when an ApplicationMediator should be initialized based on another ApplicationMediator's contents.
isValid	public abstract boolean isValid()	Invoked when the ApplicationMediator's state needs to be checked to see if it is valid.
isVisible	public abstract boolean isVisible()	Invoked to see if the ApplicationMediator is visible.
refresh	public abstract void refresh (Object data)	Invoked to supply new or changed data.
removePlacementListener	public abstract void removePlacementListener (PlacementListener listener)	Invoked to remove a PlacementListener.
removeRequestListener	public abstract void removeRequestListener (RequestListener listener)	Invoked to remove a RequestListener
removeTopListener	public final void removeTopListener (TopListener listener)	Removes the TopListener.
removeViewListener	public abstract void removeViewListener (ViewListener listener)	Invoked to remove a ViewListener.
setPermissions	public abstract void setPermissions (Hashtable permissions)	Invoked to set the permissions keys and values.
setProperties	public abstract void setProperties (Properties properties)	Invoked to set the properties.
setResources	public abstract void setResources (ResourceBundle bundle)	Invoked to set the resources.
setVisible	public abstract void setVisible (boolean visible)	Invoked to set the visibility.

Figure 17A ApplicationMediatorImpl

1700

Variables		
Name	Declaration	Description
placementListeners	protected Vector placementListeners	The PlacementListeners.
topListeners	protected TopListener topListener	The TopListener
requestListeners	protected Vector requestListeners	The RequestListeners.
viewListeners	protected Vector viewListeners	The ViewEventListeners
viewController	protected Vector viewController	Whenever view controllers are created, it is by convention they will be added to this array.
applicationMediators	protected Vector applicationMediators	Whenever application mediators are created, it is by convention they will be added to this array.
data	protected Object data	This is a reference to the system data model.
requestEvent	protected RequestEvent requestEvent	This is a reference to a RequestEvent.

Figure 17B

1702

Constructors		
Name	Declaration	Description
ApplicationMediatorImpl	public ApplicationMediatorImpl()	Constructor. By changing commented code, you can switch between threading styles 1 and 2.

Figure 17C

ApplicationMediatorImpl

1704

Methods

Name	Declaration	Description
addPlacementListener	public final void addPlacementListener(PlacementListener listener)	Add a PlacementListener.
addRequestListener	public final void addRequestListener(RequestListener listener)	Add a RequestListener.
addTopListener	public final void addTopListener(TopListener listener)	Add a TopListener.
addViewListener	public final void addViewListener(ViewListener listener)	Add a ViewListener.
clear	public void clear()	Clear the ApplicationMediator by clearing all allocated ViewControllers and ApplicationMediators. All data is set to null, but lists are not destroyed. A 'cleared' ApplicationMediator can be used again. If this method is overridden in a subclass, be sure to invoke super.clear();
exit	public void exit()	Exit the ApplicationMediator by exiting all allocated ViewControllers and ApplicationMediators. All data is set to null, and lists are destroyed. An 'exited' ApplicationMediator cannot be used again. If this method is overridden in a subclass, be sure to invoke super.exit();
firePlacementEvent	protected final void firePlacementEvent(PlacementEvent event)	Notify the PlacementListeners.
fireRequestEvent	protected final void fireRequestEvent(RequestEvent event)	Notify the RequestListeners - synchronous
fireRequestEvent	protected final void fireRequestEvent(RequestEvent event, RequestResponseListener caller) throws RequestException	Notify the RequestListeners - asynchronous.
fireTopEvent	protected final void fireTopEvent(TopEvent event)	Notify the TopListeners.
fireTopListener		
fireViewEvent	protected final void fireViewEvent(ViewEvent event)	Notify the ViewListeners.
getAM	protected ApplicationMediator getAM(int i)	Return the i'th ApplicationMediator
getUTCs	public Vector getUTCs()	Return a vector of all ThinClient objects. By default, this is a Vector containing the created ViewControllers and ApplicationMediators.
getPermissions	public String[] getPermissions()	Get the settable permission keys. By default, return the class names of all allocated ViewControllers and ApplicationMediators.
getVC	protected ViewController getVC(int i)	Return the i'th ViewController
init	public void init()	Initialize the ApplicationMediator, nothing to do by default.
init	public void init(ApplicationMediator applicationMediator)	Initialize the ApplicationMediator using the listeners of an existing ApplicationMediator.
initApplicationMediators	public final void initApplicationMediators(String classNames[]) throws ClassNotFoundException, InstantiationException, IllegalAccessException	For each ApplicationMediator classname, load it, new it and add myself as a ViewEvent. The Factory class is used as a helper class.
initViewControllers	public final void initViewControllers(String classNames[]) throws ClassNotFoundException, InstantiationException, IllegalAccessException	For each ViewController classname, load it, new it and add myself as a ViewEvent. The Factory class is used as a helper class.
isEnabled	public boolean isEnabled()	Is the ApplicationController enabled?
isValid	public boolean isValid()	Return the AND'ed value of calling isValid on ApplicationMediators and ViewControllers.
isVisible	public boolean isVisible()	Is the ApplicationController visible? Hardly, since it is a non visible class. But this looks to see if any of its ViewControllers are visible. Not really, they were all set to visible/invisible via the setVisible method and we remembered the state to return here.
processViewEvent	public abstract void processViewEvent(ViewEvent e)	Deliver the ViewEvent to the subclass via this method.
refresh	public void refresh(Object data)	When new data arrives allow the ViewControllers and ApplicationControllers to be refreshed also.

Figure 17D ApplicationMediatorImpl
(continued)

Methods

Name	Declaration	Description
removePlacementListener	public final void removePlacementListener(PlacementListener listener)	Removes the PlacementListener.
removeRequestListener	public final void removeRequestListener(RequestListener listener)	Removes the RequestListener.
removeViewListener	public final void removeViewListener(ViewListener listener)	Removes the ViewListener.
requestException	public void requestException(RequestException yikes)	Called back because an asynchronous request has thrown an Exception. By default, print the message to System.err.
requestResponse	public void requestResponse(RequestEvent response)	Called back with the results of an asynchronous request.
run2	public final void run2()	By default, call refresh with the data in the response. This method is used in style 1 threading. Rename this to run() and uncomment the code as described in the class javadoc.
setAM	public void setAM(ApplicationMediator applicationMediator, int i)	Set the i'th ApplicationMediator
setEnabled	public void setEnabled(boolean toggle)	Call setEnabled on each ViewController and ApplicationMediator.
setPermissions	public void setPermissions(Hashtable permissions)	Set the permissions. By default, call setPermissions on each ViewController and ApplicationMediator.
setProperties	public void setProperties(Properties properties)	Set the properties. By default, call setProperties on each ViewController and ApplicationMediator.
setResources	public void setResources(ResourceBundle bundle)	Set the resources. By default, call setResources on each ViewController and ApplicationMediator.
setVC	public void setVC(ViewController viewController, int i)	Set the i'th ViewController
setVisible	public void setVisible(boolean visible)	Set visible on each ViewController and ApplicationMediator.
toString	public String toString()	Return the class name of the ApplicationController instance.
viewEventPerformed	public void viewEventPerformed(ViewEvent e)	A ViewEvent is delivered. Process it using Threading style 1 or 2. In the end, the processViewEvent will be called on the subclass.

ApplicationMediatorImpl.exit(): AUS8-1999-0694

```
/**
 * Exit the ApplicationMediator by exiting all allocated ViewControllers
 * and ApplicationMediators. All data is set to null, and lists are
 * destroyed. An 'exited' ApplicationMediator cannot be used again.
 * If this method is overridden in a subclass, be sure to invoke
 * super.exit();
 */
public void exit() {
    synchronized (this) {
        /* Used for style 1 event dispatching. Leave this code commented. */
        //if (this.eventThread != null) {
        //    try {
        //        eventThread.stop();
        //    } catch (Exception e) {
        //        //
        //    }
        //}

        /* Used for style 2 event dispatching. Leave this code commented. */
        for (int i = 0; i < runningThreads.size(); i++) {
            ((ApplicationMediatorThread) runningThreads.elementAt(i)).stop();
        }
        runningThreads.removeAllElements();
        viewListeners.removeAllElements();
        try {
            for (int i = 0; i < viewControllers.size(); i++) {
                ((ViewController) viewControllers.elementAt(i)).setEnabled(false);
                ((ViewController) viewControllers.elementAt(i)).exit();
            }
            for (int i = 0; i < applicationMediators.size(); i++) {
                ((ApplicationMediator) applicationMediators.elementAt(i)).setEnabled(false);
                ((ApplicationMediator) applicationMediators.elementAt(i)).exit();
            }
        } catch (Exception noProblem) {
        }
        viewControllers = null;
        applicationMediators = null;
        runningThreads = null;
        runningThreads = null;
        data = null;
    }
}
```

Figure 17E

ApplicationMediatorImpl.clear();AUS8-1999-0694

```
/**
 * Clear the ApplicationMediator by clearing all allocated ViewControllers
 * and ApplicationMediators. All data is set to null, but lists are
 * not destroyed. A 'cleared' ApplicationMediator can be used again.
 * If this method is overridden in a subclass, be sure to invoke
 * super.clear();
 */
public void clear() {
    synchronized (this) {

        /* Used for style 1 event dispatching. Leave this code commented. */
        //if (this.eventThread != null) {
        //    try {
        //        eventThread.stop();
        //    } catch (Exception e) {
        //    }
        //}

        /* Used for style 2 event dispatching. Leave this code commented. */
        for (int i = 0; i < runningThreads.size(); i++) {
            ((ApplicationMediatorThread) runningThreads.elementAt(i)).stop();
        }
        runningThreads.removeAllElements();

        //
        try {
            for (int i = 0; i < viewControllers.size(); i++) {
                ((ViewController) viewControllers.elementAt(i)).setEnabled(false);
                ((ViewController) viewControllers.elementAt(i)).clear();
            }
            for (int i = 0; i < applicationMediators.size(); i++) {
                ((ApplicationMediator) applicationMediators.elementAt(i)).setEnabled(false);
                ((ApplicationMediator) applicationMediators.elementAt(i)).clear();
            }
        } catch (Exception noRealProblemo) {
        }
        viewControllers = null;
        applicationMediators = null;
        data = null;
        viewListeners.removeAllElements();
    }
}
```

```

/**
 * Initialize the ApplicationMediator using the listeners of an
 * existing ApplicationMediator.
 */
public void init(ApplicationMediator applicationMediator) {
    if (applicationMediator instanceof ApplicationMediatorImpl) {
        ApplicationMediatorImpl a = (ApplicationMediatorImpl) applicationMediator;
        requestListeners = (Vector) a.requestListeners.clone();
        placementListeners = (Vector) a.placementListeners.clone();
        topListeners = (Vector) a.topListeners.clone();
        addViewListener(a);
    }
    init();
}

```

1710

Figure 17G

Figure 17H

```

/**
 * When new data arrives allow the ViewControllers
 * and ApplicationController to be refreshed also.
 */
public void refresh(Object data) {
    this.data = data;
    try {
        synchronized (viewController) {
            for (int j = 0; j < viewController.size(); j++) {
                ((ViewController) viewController.elementAt(j)).
                    refresh(data);
            }
        }
    } catch (Exception noRealProblem) {
    }
    try {
        synchronized (applicationMediators) {
            for (int j = 0; j < applicationMediators.size(); j++) {
                ((ApplicationMediator) applicationMediators.
                    elementAt(j)).refresh(data);
            }
        }
    } catch (Exception noRealProblem) {
    }
}

```

```

/**
 * A ViewEvent is delivered. Process it using Threading style 1 or 2. In
 * the end, the processViewEvent will be called on the subclass.
 */
public void viewEventPerformed(ViewEvent e) {
    /* Used for style 2 event dispatching, start an inner class thread */
    ApplicationMediatorThread t = new ApplicationMediatorThread(e);
    runningThreads.addElement(t);
    t.start();

    /* Used for style 1 event dispatching. Leave this code commented. */
    //ViewEvent saved = saveViewEvent(e);
    //if (eventThread == null || !eventThread.isAlive()) {
    //    finished = false;
    //    eventThread = new Thread(this);
    //    eventThread.start();
    //}
    //synchronized (this) {
    //    notify();
    //}
}

```

Figure 171

```

/**
 * This method is used in style 1 threading. Rename this to run()
 * and uncomment the code as described in the class javadoc.
 */
public final void run2() {
    /* Used for style 1 event dispatching. Leave this code commented. */
    /*
    while (true) {
        ViewEvent event = null;
        event = getViewEvent();
        if (event != null) {
            handleViewEvent(event);
        } else {
            waitForEvent();
            if (finished) {
                //something went wrong with the thread so hose this loop
                break;
            }
        }
    }
    */
}

```

1714

Figure 17J

```

/**
 * Private class to handle executions of ViewEvents() on another thread.
 */
private class ApplicationMediatorThread extends Thread {
    /**
     * The current event
     */
    private ViewEvent event;
    /**
     * Create an ApplicationMediatorThread to process the ViewEvent
     */
    public ApplicationMediatorThread(ViewEvent event) {
        super();
        this.event = event;
    }
    /**
     * Just call the handleViewEvent method that the subclass will override
     */
    public void run() {
        processViewEvent(event);
    }
}

```

Figure 17K

```

/**
 * Save the current ViewEvent on a Q
 */
private final ViewEvent saveViewEvent(ViewEvent e) {
    /* Used for style 1 event dispatching. Leave this code commented. */
    //return viewEventQueue.add(e);
    return null;
}

/**
 * Method: return the first view event saved. Used by the Q'ing system.
 */
private ViewEvent getViewEvent() {
    /* Used for style 1 event dispatching. Leave this code commented. */
    //return (ViewEvent) viewEventQueue.remove();
    return null;
}

```

1714

Figure 17L

Figure 18A

1800 PlacementEvent

Variables		Description
Name	public static final String _copyright	(c) International Business Machines Inc., 1997 1998 1999. All rights reserved.
PLACEMENTEVENT_FIRST	public static final int PLACEMENTEVENT_FIRST	
ADD	public static final int ADD	
REMOVE	public static final int REMOVE	
MODIFY	public static final int MODIFY	
PLACEMENTEVENT_LAST	public static final int PLACEMENTEVENT_LAST	
major	protected int major	The placementevent code
minor	protected int minor	the placementevent option
component	protected Object component	Component Reference
data	protected Object data	Data reference

Figure 18B

1802

Constructors		Description
Name	public PlacementEvent()	Constructs a PlacementEvent
PlacementEvent	public PlacementEvent(Object source, Object component)	Constructs a PlacementEvent
PlacementEvent	public PlacementEvent(Object source, Object component, int major)	Constructs a PlacementEvent
PlacementEvent	public PlacementEvent(Object source, Object component, int major, int minor)	Constructs a PlacementEvent
PlacementEvent	public PlacementEvent(Object source, Object component, int major, int minor, Object data)	Constructs a PlacementEvent

Figure 18C

1804

Methods		Description
Name	public final Component GetComponent()	Return the Component
GetComponent	public final Object GetData()	Return the data
GetComponent	public final int GetMajor()	Return the major code
GetComponent	public final int GetMinor()	Return the minor code
GetComponent	public final Object GetSource()	Gets the event source
GetComponent	public final void setComponent(Component component)	Sets the Component
GetComponent	public final void setData(Object data)	Set the data
GetComponent	public final void setMajor(int code)	Set the major code
GetComponent	public final void setMinor(int code)	Set the minor code
GetComponent	public final void setSource(Object source)	Set the event source
GetComponent	public String toString()	Returns a string representation of the object.

FIGURE 19A

PlacementListener

Variables

1900	
Name	Description
copyright	(c) International Business Machines, Inc. 1997 1998 1999. All rights reserved.

FIGURE 19B

Methods

1902	
Name	Description
placementEventPerformed	Invoked when we are being called to add/remove/modify a component. Do it.

TopEvent

FIGURE 20A

Variables

2000

Name	Declaration	Description
copyright	public static final String copyright	(c) International Business Machines Inc., 1997 1998 1999. All rights reserved.
TOPEVENT_FIRST	public static final int TOPEVENT_FIRST	
EXIT	public static final int EXIT	
BROWSER	public static final int BROWSER	
TITLE	public static final int TITLE	
STATUS	public static final int STATUS	
OS	public static final int OS	
A	public static final int A	
B	public static final int B	
C	public static final int C	
D	public static final int D	
E	public static final int E	
F	public static final int F	
TRACE	public static final int TRACE	
DEBUG	public static final int DEBUG	
LOG	public static final int LOG	
HOOKAWT	public static final int HOOKAWT	
HOOKJTC	public static final int HOOKJTC	
TOPEVENT_LAST	public static final int TOPEVENT_LAST	
TEAM	public static final int TEAM	
WIN	public static final int WIN	
EXECUTE	public static final int execute	
consumed	protected boolean consumed	Is event still valid?
data	protected Object data	This is a loose reference to the data model. We don't care what the class shape is and we only reference it via the interface that it must implement.

TopEvent

FIGURE 20B

2002

Constructors

Name	Declaration	Description
TopEvent()	public TopEvent()	Default constructor for a Request
TopEvent(Object)	public TopEvent(Object source)	Construct with the given source and default major and minor values.
TopEvent(Object, int)	public TopEvent(Object source, int major)	Create a Request with a source, major and minor codes.
TopEvent(Object, int, int)	public TopEvent(Object source, int major, int minor)	Create a Request with major and minor codes.
TopEvent(Object, int, int, Object)	public TopEvent(Object source, int major, int minor, Object data)	Create a Request with a source, major and minor codes, and some data. If source is null, an InvalidArgumentException will be thrown.

FIGURE 20C

2004

Methods

Name	Declaration	Description
consume	public final void consume()	Consume this event
getData	public final Object getData()	Return the reference to the data.
getMajor	public final int getMajor()	Get the major code.
getMinor	public final int getMinor()	Get the minor code.
getSource	public final Object getSource()	Gets the event source.
isConsumed	public final boolean isConsumed()	Overrides: getSource in class EventObject
setConsumed	public final void setConsumed(boolean consumed)	Is the event consumed?
setData	public final void setData(Object data)	Turn event consumed on or off.
setMajor	public final void setMajor(int major)	Set the data.
setMinor	public final void setMinor(int minor)	Set the major code.
setSource	public final void setSource(Object source)	Set the minor code. This is always a String.
toString	public String toString()	Gets the event source.
		Show a String representation of the Request in the format of "TopEvent(major,minor)"

TopListener

FIGURE 21A

Variables

Name	Declaration	Description
copyright	public static final String copyright	(c) International Business Machines, Inc., 1997 1998 1999. All rights reserved.

2100

Methods

Name	Declaration	Description
exec	public abstract void exec (Object programInformation)	Invoked to execute a desktop program. The parameter programInformation can be a complex object with lots of data. For example: String[] params = {"netscape.exe", "http://www.ibm.com/"}; aTopListener.exec(params). Another usage might be to interact with JavaScript under a browser. It is up to the TopListener implementer to understand what the params mean. Do not create a language with a language. This method should only be defined to support legacy environments or corporate desktop rules. Consider using a RequestEvent for more complex requirements.
exit	public abstract void exit()	Invoked to exit a JTC application. Never let a program perform its own "exit". This shuts the JVM down. The implementer of TopListener will know the appropriate actions to take to exit from an application on a corporate desktop.
message	public abstract void message (Object messageInfo)	Invoked to show a business specific message. Try to isolate calls to the browser here.
title	public abstract void title (Object titleInfo)	Invoked to display a business specific title. Try to isolate calls to a browser or a desktop program to display titles here.
topEventPerformed	public abstract void topEventPerformed (TopEvent event)	Invoked when we are being called to perform a top desktop function.

2102

RequestEvent

Figure 22A

2200

Variables		Description	
Name	Declaration		
copyright	public static final String copyright		© International Business Machines Inc., 1997-1998-1999. All rights reserved.
consumed	protected boolean consumed		Is event still valid
data	protected Object data		This is a loose reference to the data model. We don't care what the class shape is and we only reference it via the interface that it must implement.

Figure 22B

2202

Constructors		Description	
Name	Declaration		
RequestEvent	public RequestEvent()		Default constructor for a Request.
RequestEvent	public RequestEvent(Object source)		Construct with the given source and default major and minor values.
RequestEvent	public RequestEvent(Object source, String major)		Create a Request with a source, major and minor codes.
RequestEvent	public RequestEvent(Object source, String major, String minor)		Create a Request with major and minor codes.
RequestEvent	public RequestEvent(Object source, String majorCode, String minorCode, Object data)		Create a Request with a source, major and minor codes, and some data. If source is null, an InvalidArgumentException will be thrown.

Figure 22C

2204

Methods		Description	
Name	Declaration		
consume	public final void consume()		Consume this event.
getData	public final Object getData()		Return the reference to the data.
getMajor	public final String getMajor()		Get the major code. This is always a String.
getMinor	public final String getMinor()		Get the minor code. This is always a String.
getSource	public final Object getSource()		Gets the event source.
getStatus	public final String getStatus()		Return the status.
isConsumed	public final boolean isConsumed()		Is the event consumed?
setConsumed	public final void setConsumed(boolean consumed)		Turn event consumed on or off.
setData	public final void setData(Object data)		Set the data.
setMajor	public final void setMajor(String major)		Set the major code. This is always a String.
setMinor	public final void setMinor(String minor)		Set the minor code. This is always a String.
setSource	public final void setSource(Object source)		Set the event source.
setStatus	public final void setStatus(String message)		Append a message to the status.
toString	public String toString()		Show a String representation of the Request in the format of "RequestEvent(major,minor)"

Figure 23A

RequestException

Variables		
Name	Declaration	Description
copyright	public static final String copyright	(c) International Business Machines Inc., 1997 1998 1999. All rights reserved.

2300

Figure 23B

2302

Constructors		
Name	Declaration	Description
RequestException	public RequestException()	Default constructor.
RequestException	public RequestException(String s)	Constructor with a message to the request exception.
RequestException	public RequestException(Throwable target)	Constructor with a throwable target
RequestException	public RequestException(Throwable target, String s)	Constructor with a throwable target and a message

Figure 23C

2304

Methods		
Name	Declaration	Description
getTargetException	public Throwable getTargetException()	Get the target throwable
setTargetException	public void setTargetException(Throwable target)	Set the target throwable
toString	public String toString()	String version

RequestListener

FIGURE 24A

Variables

Name	Declaration	Description
copyright	public static final String copyright	(c) International Business Machines, Inc., 1997 1998 1999. All rights reserved.

2400

FIGURE 24B

Methods

Name	Declaration	Description
requestEventPerformed	public abstract void requestEventPerformed (RequestEvent request) throws RequestException	Invoked for a synchronous RequestEvent.
requestEventPerformed	public abstract void requestEventPerformed (RequestEvent request, RequestResponseListener listener) throws RequestException	Invoked for an asynchronous RequestEvent.

2402

RequestResponseListener

FIGURE 25A

Variables

		2500
Name	Declaration	Description
copyright	public static final String copyright	(c) International Business Machines, Inc., 1997 1998 1999. All rights reserved.

FIGURE 25B

Methods

		2502
Name	Declaration	Description
requestException	public abstract void requestException (RequestException yikes)	Invoked when an exception occurred during processing of an asynchronous RequestEvent.
requestResponse	public abstract void requestResponse (RequestEvent result)	Invoked when the processing of an asynchronous RequestEvent was successful.

Figure 26A

Transporter

Variables		2600	
Name	Declaration	Description	
copyright	public static final String copyright	(c) International Business Machines Inc., 1997 1998 1999. All rights reserved.	
PRIORITY	public static final String PRIORITY	Priority symbol	
WILDCARD	public static final String WILDCARD	Wildcard symbol	

Figure 26B

Constructors		
Name	Declaration	Description
Transporter	public Transporter()	Default constructor.

Figure 26C

Transporter

2604

Methods

Name	Declaration	Description
addDestinationListener	public void addDestinationListener(Object major, Destination destination)	Add the Destination using the given major code. If the destination is present with the same major don't re-add it - only one major/destination pair can exist. If the major is present, but the destination isn't, add the destination to the list of other destinations with the same key. If the key isn't present, store it and then add the new destination. If the destination is disabled, do nothing.
clear	public void clear()	For each RequestEvent not started, a RequestException will be thrown and the internal data structures will be emptied including RequestEvent queues and listeners.
exit	public void exit()	For each RequestEvent not started, a RequestException will be thrown and the internal data structures will be emptied including RequestEvent queues and listeners. All variable references will be set to null.
getDestinations	public synchronized Vector getDestinations()	Return a Vector of all Destinations currently registered.
getDestinations	public Vector getDestinations(Object major)	Return a Vector of the Destinations currently registered for the given major code
getJTCs	public Vector getJTCs()	Return allocated JTC objects. By default, return the Destinations.
getMajorCodes	public Vector getMajorCodes()	Return a Vector of the registered major codes
init	public void init()	Initialize the transporter. By default, do nothing.
isEnabled	public boolean isEnabled()	Is this Transporter enabled or disabled? A Transporter that is disabled will not process an RequestEvents but will throw RequestExceptions.
isTagging	public boolean isTagging()	Is this Transporter tagging RequestEvents?
processDestinations	protected void processDestinations(RequestEvent request, Vector currentDestinations) throws RequestException	Given a RequestEvent and a Vector of destinations, call each Destination in FIFO/FEFR order. If tagging is enabled, then append a status tag to the RequestEvent.
removeDestinationListener	public void removeDestinationListener(Object major, Destination d)	Remove the destination using the given major. If the destination is not present, do nothing. If the destination is present, just remove it. If it was the last destination, remove all references to the major code.
requestEventPerformed	public void requestEventPerformed(RequestEvent request) throws RequestException	Submit a synchronous request. For each Destination that is listening for the current family of RequestEvents (the major code), send the RequestEvent to the Destination for processing. If there is a problem, throw a RequestException. Continue processing the RequestEvent as long as a RequestException is not thrown by a Destination and the RequestEvent is not consumed. If tagging is enabled, then append a status tag to the RequestEvent. Destinations are process in the following FIFO order: 1- All using "i" (priority). 2- All using a major code. 3- All using "a".
requestEventPerformed	public void requestEventPerformed(RequestEvent request, RequestResponseListener caller) throws RequestException	Submit an asynchronous request. See the synchronous requestEventPerformed for more information.
setEnabled	public void setEnabled(boolean toggle)	Enabled or disabled the Transporter. A disabled Transporter will throw RequestExceptions if accessed via requestEventPerformed.
setRequestTagging	public void setRequestTagging(boolean toggle)	Stop or start the tagging of Requests.
toString	public String toString()	Return the String Transporter plus the number of registered Destinations.

Transporter.processDestinations(RequestEvent Vector):AUS8-1999-0693

```

/**
 * Given a RequestEvent and a Vector of destinations, call each Destination
 * in FIFO/FEFR order.
 * <p>
 * If tagging is enabled, then append a status tag to the RequestEvent.
 * @exception RequestException if the Request can't be submitted
 */
protected void processDestinations(RequestEvent request, Vector currentDestinations) throws RequestException {
    if (!enabled) {
        throw new RequestException("Transporter disabled");
    }
    if (currentDestinations == null)
        return;

    /* process FIFO/FEFR */
    Destination d = null;
    int size = currentDestinations.size();
    for (int i = 0; !request.isConsumed() && i < size; i++) {
        d = (Destination) currentDestinations.elementAt(i);
        d.requestEventPerformed(request);
        /* Try to tag the request */
        if (tagging)
            request.setStatus(request.getStatus() + d);
    }
}

```

Figure 26D

Transporter.requestEventPerformed(RequestEvent);AUS8-1999-0693

```

/**
 * Submit a synchronous request. For each Destination that is listening for
 * the current family of RequestEvents (the major code), send the RequestEvent
 * to the Destination for processing. If there is a problem, throw
 * a RequestException. Continue processing the RequestEvent as long
 * as a RequestException is not thrown by a Destination and the RequestEvent
 * is not consumed.
 * <p>
 * If tagging is enabled, then append a status tag to the RequestEvent.
 * <p>
 * Destinations are process in the following FIFO order:
 * 1- All using "!" (priority).
 * 2- All using a major code.
 * 3- All using "".
 * <p>
 * @exception RequestException if the Request can't be submitted
 */
public void requestEventPerformed(RequestEvent request) throws RequestException {
    if (!enabled) {
        throw new RequestException("Transporter disabled");
    }

    /* Try to tag the request */
    if (tagging)
        request.setStatus(request.getStatus() + "[Transporter]");

    /* Process PRIORITY, major and then WILDCARD destinations */
    processDestinations(request, getDestinations(PRIORITY));
    processDestinations(request, getDestinations(request.getMajor()));
    processDestinations(request, getDestinations(WILDCARD));
}

```

2606

Figure 26E

```

/**
 * Submit an asynchronous request. See the synchronous
 * requestEventPerformed for more information.
 */
public void requestEventPerformed(RequestEvent request,
RequestEventListener caller) throws RequestException {
    if (!enabled) {
        throw new RequestException("Transporter disabled");
    }
    if (tagging)
        request.setStatus(request.getStatus() +
            "Transporter async.");

    //start an inner class thread
    TransporterThread t = new TransporterThread(request, caller);
    runningThreads.put(request, t);
    t.start();
}

```

Figure 26F

TransporterThread:AUS8-1999-0693

```

/**
 * Private class to handle executions of submits() on another
 * thread.
 */
private class TransporterThread extends Thread {
/**
 * The current request
 */
private RequestEvent request;

/**
 * The caller of submit that we will call back
 */
private RequestEventListener caller;

/**
 * Create a transporter thread
 */
public TransporterThread(RequestEvent request,
RequestEventListener caller) {
    super();
    this.request = request;
    this.caller = caller;
}

/**
 * Just call the synchronous version of
 * requestEventPerformed()
 */
public void run() {
    try {
        requestEventPerformed(request);
        caller.requestResponse(request);
    } catch (RequestException yikes) {
        caller.requestException(yikes);
    } finally {
        runningThreads.remove(request);
    }
}
}

```

2610

Figure 26G

Figure 27A

Destination

Variables		
Name	Declaration	Description
copyright	public static final String copyright	(c) International Business Machines Inc., 1997, 1998, 1999. All rights reserved.

Figure 27B

Methods

Name	Declaration	Description
getTimeout	public abstract long getTimeout()	Invoked to return the timeout value.
requestEventPerformed	public abstract void requestEventPerformed (RequestEvent request) throws RequestException	Invoked to process a RequestEvent.
setTimeout	public abstract void setTimeout(long timeout)	Invoked to set the timeout value in ms.

Figure 28A

DestinationImpl

Variables

Name	Declaration	Description
copyright	public static final String copyright	(c) International Business Machines Inc., 1997 1998 1999. All rights reserved.

Figure 28B

2802

Constructors

Name	Declaration	Description
DestinationImpl	public DestinationImpl()	Default constructor.

Figure 28C

2804

Methods

Name	Declaration	Description
clear	public void clear()	By default, do nothing.
exit	public void exit()	By default, do nothing.
getJTCs	public Vector getJTCs()	By default, do nothing.
getTimeout	public long getTimeout()	Return the timeout value.
init	public void init()	By default, do nothing.
isEnabled	public boolean isEnabled()	Is the Destination enabled?
requestEventPerformed	public void requestEventPerformed(RequestEvent request) throws RequestException	A RequestEvent has arrived. If not enabled, throw and exception. Subclasses can call this method first to see if processing should continue.
setEnabled	public void setEnabled(boolean enable)	Enable or disable the Destination. A Destination that is called when disable will throw a RequestException. By default, record it.
setTimeout	public void setTimeout(long timeout)	Set the timeout value. By default, record it.
toString	public String toString()	Returns a String that represents the value of this object which is the class name and the timeout value.

RemoteDestination.requestEventPerformed(RequestEvent)-AUS8-1999-0704

```

/**
 * Process request event.
 *
 * <P>PRE: None
 * <P>POST: None
 *
 * @param request the RequestEvent object to be processed.
 * @exception RequestException if there was an error during the
 *         processing of the event.
 */
public void requestEventPerformed(RequestEvent request) throws
RequestException {
    try {
        Method method = null;
        if (session == null) {
            // get home interface.
            Context ctxt = getInitialContext();
            Object home = ctxt.lookup(request.getMajor() +
"SessionHome");

            method = home.getClass().getMethod("create", null);
            session = method.invoke(home, null);
        }

        // get method on home object and invoke it.
        method = session.getClass().getMethod(request.getMinor(),
            new Class[] {Object.class});
        request.setData(method.invoke(session, new Object[]
{request.getData()}));

        if (request.getMinor().equals("remove")) {
            session = null;
        }
        catch (InvocationTargetException te) {
            throw new RequestException(te.getTargetException());
        }
        catch (Throwable t) {
            throw new RequestException(t);
        }
    }
}

```

2806

Figure 28D

Figure 29A

Factory

Variables

Name	Declaration	Description
copyright	public static final String copyright	(c) International Business Machines Inc., 1997 1998 1999. All rights reserved.

2900

Figure 29B

Methods

Name	Declaration	Description
list	public static void list()	Show the contents of the singletons
newInstance	public static Object newInstance(String classname) throws ClassNotFoundException, InstantiationException, IllegalAccessException	Given a class name, create it and return it.
newInstance	public static Object newInstance(String classname, String key, boolean singleton) throws ClassNotFoundException, InstantiationException, IllegalAccessException	Given a class name, create the object and return it. If you want to create a singleton (true), then check to see if the object was already created and if so, return it. The class name is not used as the key but the "key" parameter is.
newInstance	public static Object newInstance(String classname, boolean singleton) throws ClassNotFoundException, InstantiationException, IllegalAccessException	Given a class name, create the object and return it. If you want to create a singleton (true), then check to see if the object was already created and if so, return it. Use the class name as the key.
newInstance	public static Vector newInstance(String classnames[]) throws ClassNotFoundException, InstantiationException, IllegalAccessException	Given some class names, create and return a Vector of objects.
newInstance	public static Vector newInstance(String classnames[], String keys[], boolean singleton) throws ClassNotFoundException, InstantiationException, IllegalAccessException	Given some class names, create and return a Vector of objects. If you want singleton objects system wide, then if any of the classes were already created, return them, otherwise, create the new ones, remember them and return them. The class names are not used as the keys but the "keys" parameter are.
newInstance	public static Vector newInstance(String classnames[], boolean singleton) throws ClassNotFoundException, InstantiationException, IllegalAccessException	Given some class names, create and return a Vector of objects. If you want singleton objects system wide, then if any of the classes were already created, return them, otherwise, create the new ones, remember them and return them. Use the class name as the key.
removeInstances	public static void removeInstances(String key) throws ClassNotFoundException, InstantiationException, IllegalAccessException	Given a class key, clear the reference to it.
removeInstances	public static void removeInstances(String keys[]) throws ClassNotFoundException, InstantiationException, IllegalAccessException	Given some class keys, clear the references.

2902

Interface com.ibm.jtc.JTC

3000

FIGURE 30A

Variables		
Name	Declaration	Description
<code>_copyright</code>	<code>Public static final String _copyright</code>	International Business Machines Inc., 1997 1998 1999. All rights reserved.
<code>_version</code>	<code>Public static final String version</code>	
<code>_author</code>	<code>Public static final String _author</code>	
<code>_email</code>	<code>Public static final String _email</code>	

FIGURE 30B

3002

Methods		
Name	Declaration	Description
<code>clear</code>	<code>Public abstract void clear()</code>	Invoked to indicate that all memory allocations should be cleaned up. This includes removing listeners and flushing any lists (vectors or hashables). A JTC object that has been cleared can be reused.
<code>exit</code>	<code>public abstract void exit()</code>	Invoked to indicate that all memory allocations should be cleaned up. This includes removing listeners and flushing any lists (vectors or hashables). It also includes setting all variable references to null. A JTC object that has been cleared cannot be reused.
<code>getJTCs</code>	<code>Public abstract Vector getJTCs()</code>	Invoked to get a Vector of all JTC objects that this JTC object has created. For example, a Transporter will at least return all of its Destinations. This is a very powerful mechanism. It allows us to get a reference to all primary objects in the JTC application and manipulate them according to the JTC methods, or by casting them to more specific classes or interfaces and manipulating them. Examples usage includes non code intrusive tracing, debugging, logging, profiling, etc.
<code>init</code>	<code>Public abstract void init()</code>	Invoked to initialize the JTC object. The object should be ready for operation.
<code>isEnabled</code>	<code>Public abstract boolean isEnabled()</code>	Invoked to determine if the JTC object is enabled.
<code>setEnabled</code>	<code>Public abstract void setEnabled(boolean enable)</code>	Invoked to enable or disable the JTC object.
<code>toString</code>	<code>Public abstract String toString()</code>	Invoked to get a String representation of the JTC object.

Figure 31

View Controller




Figure 32

Create Validation Rule




Figure 33

Create a ViewEvent




Figure 34

Create ApplicationMediator




Figure 35

Create RequestEvent




Figure 36

Create a Destination




Figure 37

Create TopListener






Figure 38

Create PlacementListener



ViewController runtime

Figure 39







FIGURE 40

**Basic Operation of a
ViewControllerImpl**

Figure 41



View Event and View Listener Usage

FIGURE 42

```

→ Usage from a ViewController
public void actionPerformed(ActionEvent) {
    if (e.getSource() == nextButton) {
        ViewEvent ve = new ViewEvent (this);
        ve.setMajor(ViewEvent.NEXT);
        fireEvent(ve); //notify
        ViewEvent listener
            return;
    }
}

```

FIGURE 43

```

→ Usage from ViewListener (i.e. ApplicationMediator)
//add myself as a listener
customerDetailsViewController.addViewListener(this);

//later, we are called back on this method to handle the
ViewEvent
processViewEvent (ViewEvent event) {
    //do something
    switch (event.getMajor()) {
        case ViewEvent.NEXT: //...
            break;
        case ViewEvent.OK: //...
            break;
    }
}

```


Major and/or minor codes

FIGURE 44

- Pre-defined major codes- A subclass can define others.
 - // system
 - OK DONE OPEN CLOSE CANCEL EXIT FILE SAVE SAVEAS ERROR WARNING RETURN
LOAD NOTIFY NOTIFY2 INFO SETUP PRINT LOGIN LOGOUT ENABLE DISABLE
 - // status
 - TITLEMESSAGE STATUSMESSAGE ERRORMESSAGE SUGGESTIONMESSAGE
 - // navigational
 - NEXT PREVIOUS FIRST LAST START BEGIN END PAUSE STOP RESTART SUBMIT
BACKSPACE INSERT HOME PGUP PGDN LEFT RIGHT UP DOWN
 - // live
 - FAST MEDIUM SLOW RUN DELAY WAIT TIMER ON OFF HIGH LOW
 - // data related
 - LIST MORE ADD DELETE MODIFY NEW EDIT COPY CUT PASTE UNDO REMOVE PLUS
MINUS INCREMENT DECREMENT CHANGED FILL EMPTY READY VIEW DETAILS READ
WRITE UPDATE REFRESH
 - // assit related
 - SEARCH FIND HELP HINT TRAIN TEACH SUGGEST
 - //sub options related
 - A B C D E F OPTION CHOOSE
 - // test values
 - TRACE UNTRACE DEBUG UNDEBUG LOG UNLOG HOOK UNHOOK
 - // lbn values
 - TEAM WIN EXECUTE

ValidationRules Usage

→ Examples:

```
edit("123456")      -> $1234.56
normalize("$1234.56") -> 123456
edit("12345x")      -> ValidationRuleException
```

→ edit

```
//validate and re-display
String value = textfield.getText();
try {
    result = SocialSecurity.edit(value);
}
catch (ValidationRuleException yikes) {
    //...
    return;
}
textField.setText(value);
```

FIGURE 45

→ normalize

```
//validate and update the data objects
String value = textfield.getText();
try {
    result = SocialSecurity.normalize(value);
}
catch (ValidationRuleException yikes) {
    //message box ...
    return;
}
dataObject.setText(value);
```

FIGURE 46

ValidationRules Usage

→ Example Chaining

FIGURE 47

```
//each rule
String range = "com.xyz.jtc.RangeChecker";
String money = "com.xyz.jtc.AccountMoney";

//build the chain of rules
String[] rules = {range, money};

//get the value to validate
String value = textField.getText();

try {
    value = applyEdits(rules, input);
}
catch (ValidationRuleException ouch) {
    //...
}

//the value is validated and formatted, redisplay
textField.setText(value);
```

View ControllerBaseImpl

→ For example:

- Inheritance

FIGURE 48

```
public class ViewControllerBaseImpl extends JPanel {
    public Component getComponent() {
        return this;
    }
}
```

FIGURE 49

- delegation

```
public class ViewControllerBaseImpl implements ViewController
```

```
{
    XYZ xyz = new XYZ();


    public java.awt.Component getComponent() {
        return xyz;
    }

    public void setEnabled(boolean e) {
        xyz.setEnabled(e);
    }

    public void setVisible(boolean v) {
        xyz.setVisible(v);
    }
}
```

ApplicationMediator runtime


Figure 50



AWTEvent threading support

- Style 1 - wait / Queue / notify
- Style 2 - Thread dispatch
- Handles Threading Model for ViewControllers

Figure 51







FIGURE 52

Design Steps for an ApplicationMediator

Placement runtime

Figure 53



Placement example

→ Usage from ApplicationMediator

```
//in an ApplicationMediator
int major = PlacementEvent.ADD;
Component component =
customerDetailsViewController.getComponent();
PlacementEvent e = new PlacementEvent(this, component, major);
firePlacementEvent(e);
```

FIGURE 54

→ Usage from PlacementListener


```
public class MyProgram implements PlacementListener {
    public void placementEventPerformed(PlacementEvent e) {
        //decide based on source type
        switch (e.getMajor()) {
```

FIGURE 55

```
        case PlacementEvent.ADD:
            if (e.getSource() instanceof PreferencesAm)
                panel1.add("Center", e.getComponent());
            else panel2.add("A", e.getComponent());
            break;
        case PlacementEvent.REMOVE:
            //do something else
            break;
    }
    //etc.
}
```


FIGURE 56

**Design Steps for a
PlacementEvent**



TopListener runtime

Figure 57



TopListener example

FIGURE 58

```
//from the TopListener
ApplicationMediatorXYZ m = new ApplicationMediatorXYZ();
m.addTopListener(this);
```

FIGURE 59


```
//in the ApplicationMediator
String status = "Loading files...";
TopEvent e = new TopEvent(this, TopEvent.STATUS, 0, status);
fireTopEvent(e);
```

FIGURE 60

```
//later in the TopListener callback
public void topEventPerformed(TopEvent e) {
    switch(e.getMajor()) {
        case STATUS:
            //access the browser
            break;
            /etc.
    }
}
```

RequestEvent runtime

Figure 61



RequestEvent example

```
//from an ApplicationMediator - create event  
RequestEvent r = new RequestEvent();  
r.setMajor("Loans");  
r.setMinor("SubmitCustomerInfo");
```

FIGURE
62

```
//fire an asynchronous event  
try {  
    //asynchronous  
    fireRequestEvent(this, r);  
}  
catch (RequestException yikes) {}
```


FIGURE
63

```
//later, called back with success  
public void requestResponse(RequestEvent result) {  
    //process response  
}  
  
//or failure  
public void requestException(RequestException yikes) {  
    //now what?  
}
```

FIGURE
64

FIGURE 65


Design Steps for a
RequestEvent



Transporter

runtime

Figure 66



Transporter

- ➔ This class implements the JTC and RequestEventListener interfaces
- ➔ Its primary function is to map RequestEvents to Destinations.
 - Typically ApplicationMediators fire RequestEvents and Destinations process them
- ➔ Add a Transporter to an ApplicationMediator to listen for RequestEvents

```

Transporter t = new Transporter();
ApplicationMediator am = new ApplicationMediator();
am.addRequestListener(t);
    
```

FIGURE 67


- ➔ The ApplicationMediator will fire RequestEvents

```

RequestEvent r = new RequestEvent(source, major, minor, data);
try {
    fireRequestEvent(r);
}
catch (RequestException yikes) {}
    
```

Destination runtime

Figure 68



Destination

- ➔ RequestEvents are identified by
 - major code - represents a family of Requests
 - minor code - represents a specific Request
- ➔ Destinations are added to the Transporter as DestinationListeners
 - specifying a major code for RequestEvents they are interested in receiving
- ➔ The destination is called when the major code of the RequestEvent matches the destination major code

```
EJBDestination d = new EJBDestination();
Transporter t = new Transporter();
String major = "Loans";
t.addDestinationListener(major, d);
```

FIGURE 69

- ➔ Multiple Destinations can listen for the same RequestEvent major code
 - processed FIFO / FESP (first in first out, first exception stop forwarding)
 - results of one Destination can be passed to the next Destination

getJTCs example

FIGURE 71

```
// Recursively look at the root, find each JTC and/or AWT and hook
public void hookJTCs(JTC root) {
    Vector jtcS = null;
    try {
        jtcS = root.getJTCs();
    } catch (Exception none) { return; } // should not happen

    if (jtcS == null) return; //we are done

    int size = jtcS.size();
    for (int j = 0; j < size; j++) {
        Object current = jtcS.elementAt(j);
        if (current instanceof ApplicationMediator) {
            hookAM((ApplicationMediator) current);
        } else
            if (current instanceof ViewController) {
                hookVC((ViewController) current);
            } else
                if (current instanceof Transporter) {
                    hookTransporter((Transporter) current);
                } else
                    if (current instanceof java.awt.Component) {
                        //once into AWT tree, never back to JTCs
                        hookAWTs((java.awt.Component) current);
                        continue;
                    }
            }
        hookJTCs((JTC) jtcS.elementAt(j)); //recursive
    }
}
```

hookJTC helpers

FIGURE
72

```

/**
 * Hook the ApplicationMediator
 */
public void hookAM(ApplicationMediator am) {
    vcl.refresh("ApplicationControllers found:" + am);
    am.addViewListener(this);
    am.addRequestListener(this);
    vcl.refresh("....add as ViewListener");
    vcl.refresh("....add as RequestListener");
}

/**
 * Hook the ViewController and it's getComponent()
 */
public void hookVC(ViewController vc) {
    vcl.refresh("ViewController found:" + vc);
    vc.addViewListener(this);
    vcl.refresh("....add as ViewListener");
    hookAWTs(vc.getComponent());
}

/**
 * Hook the Transporter
 */
public void hookTransporter(Transporter transporter) {
    vcl.refresh("Transporter found:" + transporter);
    transporter.addDestinationListener("!", this);
    vcl.refresh("....add as ! DestinationListener");
}

```

hookAWTs

FIGURE 73

```
// Recursively find each AWT object and hook
public void hookAWTs(Component comp) {
    if (component instanceof Container) {
        val.refresh("Container found:" + comp);
        Component[] comps = ((Container) comp).getComponents();
        int size = comps.length;
        for (int i = 0; i < size; i++) {
            hookAWTs(comps[i]);
        }
    }
    /* continue here since some regular Components, such as JLabels,
    * are Containers also.
    */
    if (comp instanceof Button) {
        hookAWTButton((Button) comp);
    } else
        if (comp instanceof JButton) {
            hookSwingJButton((JButton) comp);
        } else
            if (component instanceof JTextField) {
                hookSwingJTextField((JTextField) comp);
            }
    /*....else do over every other Bean/Component/Container
    * type possibly using reflection or a table driven
    * implementation.
    */
}
```

hookAWTs - helpers

FIGURE

74

```
/**
 * Hook the java.awt.Button
 */
public void hookAWTButton(Button button) {
    vcl.refresh("java.awt.Button found:" + button);
    button.addActionListener(this);
    vcl.refresh("...add as ActionListener");
}

/**
 * Hook the com.sun.java.swing.JButton
 */
public void hookSwingJButton(JButton button) {
    vcl.refresh("com.sun.java.swing.JButton found:" + button);
    button.addActionListener(this);
    button.addChangeListener(this);
    button.addItemListener(this);
    vcl.refresh("...add as ActionListener");
    vcl.refresh("...add as ChangeListener");
    vcl.refresh("...add as ItemListener");
}

/**
 * Hook the com.sun.java.swing.JTextField
 */
public void hookSwingJTextField(JTextField textField) {
    vcl.refresh("com.sun.java.swing.JTextField found:" + textField);
    textField.addActionListener(this);
    textField.addChangeListener(this);
    vcl.refresh("...add as ActionListener");
    vcl.refresh("...add as CaretListener");
}
}
```





FIGURE 75

```

graph TD
    A["A  
Z600"] --> A1["A1  
Z602"]
    A --> A2["A2  
Z604"]
    A --> A3["A3  
Z606"]
    A1 --> A11["A11  
Z608"]
    A1 --> A12["A12  
Z610"]
    A3 --> A31["A31  
Z612"]
    A3 --> A32["A32  
Z614"]
  
```

2000 2001 2002 2003 2004 2005 2006 2007 2008 2009 2010 2011 2012 2013 2014 2015 2016 2017 2018 2019 2020 2021 2022 2023 2024 2025 2026 2027 2028 2029 2030 2031 2032 2033 2034 2035 2036 2037 2038 2039 2040 2041 2042 2043 2044 2045 2046 2047 2048 2049 2050 2051 2052 2053 2054 2055 2056 2057 2058 2059 2060 2061 2062 2063 2064 2065 2066 2067 2068 2069 2070 2071 2072 2073 2074 2075 2076 2077 2078 2079 2080 2081 2082 2083 2084 2085 2086 2087 2088 2089 2090 2091 2092 2093 2094 2095 2096 2097 2098 2099 2100 2101 2102 2103 2104 2105 2106 2107 2108 2109 2110 2111 2112 2113 2114 2115 2116 2117 2118 2119 2120 2121 2122 2123 2124 2125 2126 2127 2128 2129 2130 2131 2132 2133 2134 2135 2136 2137 2138 2139 2140 2141 2142 2143 2144 2145 2146 2147 2148 2149 2150 2151 2152 2153 2154 2155 2156 2157 2158 2159 2160 2161 2162 2163 2164 2165 2166 2167 2168 2169 2170 2171 2172 2173 2174 2175 2176 2177 2178 2179 2180 2181 2182 2183 2184 2185 2186 2187 2188 2189 2190 2191 2192 2193 2194 2195 2196 2197 2198 2199 2200 2201 2202 2203 2204 2205 2206 2207 2208 2209 2210 2211 2212 2213 2214 2215 2216 2217 2218 2219 2220 2221 2222 2223 2224 2225 2226 2227 2228 2229 2230 2231 2232 2233 2234 2235 2236 2237 2238 2239 2240 2241 2242 2243 2244 2245 2246 2247 2248 2249 2250 2251 2252 2253 2254 2255 2256 2257 2258 2259 2260 2261 2262 2263 2264 2265 2266 2267 2268 2269 2270 2271 2272 2273 2274 2275 2276 2277 2278 2279 2280 2281 2282 2283 2284 2285 2286 2287 2288 2289 2290 2291 2292 2293 2294 2295 2296 2297 2298 2299 2300 2301 2302 2303 2304 2305 2306 2307 2308 2309 2310 2311 2312 2313 2314 2315 2316 2317 2318 2319 2320 2321 2322 2323 2324 2325 2326 2327 2328 2329 2330 2331 2332 2333 2334 2335 2336 2337 2338 2339 2340 2341 2342 2343 2344 2345 2346 2347 2348 2349 2350 2351 2352 2353 2354 2355 2356 2357 2358 2359 2360 2361 2362 2363 2364 2365 2366 2367 2368 2369 2370 2371 2372 2373 2374 2375 2376 2377 2378 2379 2380 2381 2382 2383 2384 2385 2386 2387 2388 2389 2390 2391 2392 2393 2394 2395 2396 2397 2398 2399 2400 2401 2402 2403 2404 2405 2406 2407 2408 2409 2410 2411 2412 2413 2414 2415 2416 2417 2418 2419 2420 2421 2422 2423 2424 2425 2426 2427 2428 2429 2430 2431 2432 2433 2434 2435 2436 2437 2438 2439 2440 2441 2442 2443 2444 2445 2446 2447 2448 2449 2450 2451 2452 2453 2454 2455 2456 2457 2458 2459 2460 2461 2462 2463 2464 2465 2466 2467 2468 2469 2470 2471 2472 2473 2474 2475 2476 2477 2478 2479 2480 2481 2482 2483 2484 2485 2486 2487 2488 2489 2490 2491 2492 2493 2494 2495 2496 2497 2498 2499 2500 2501 2502 2503 2504 2505 2506 2507 2508 2509 2510 2511 2512 2513 2514 2515 2516 2517 2518 2519 2520 2521 2522 2523 2524 2525 2526 2527 2528 2529 2530 2531 2532 2533 2534 2535 2536 2537 2538 2539 2540 2541 2542 2543 2544 2545 2546 2547 2548 2549 2550 2551 2552 2553 2554 2555 2556 2557 2558 2559 2560 2561 2562 2563 2564 2565 2566 2567 2568 2569 2570 2571 2572 2573 2574 2575 2576 2577 2578 2579 2580 2581 2582 2583 2584 2585 2586 2587 2588 2589 2590 2591 2592 2593 2594 2595 2596 2597 2598 2599 2600 2601 2602 2603 2604 2605 2606 2607 2608 2609 2610 2611 2612 2613 2614 2615 2616 2617 2618 2619 2620 2621 2622 2623 2624 2625 2626 2627 2628 2629 2630 2631 2632 2633 2634 2635 2636 2637 2638 2639 2640 2641 2642 2643 2644 2645 2646 2647 2648 2649 2650 2651 2652 2653 2654 2655 2656 2657 2658 2659 2660 2661 2662 2663 2664 2665 2666 2667 2668 2669 2670 2671 2672 2673 2674 2675 2676 2677 2678 2679 2680 2681 2682 2683 2684 2685 2686 2687 2688 2689 2690 2691 2692 2693 2694 2695 2696 2697 2698 2699 2700 2701 2702 2703 2704 2705 2706 2707 2708 2709 2710 2711 2712 2713 2714 2715 2716 2717 2718 2719 2720 2721 2722 2723 2724 2725 2726 2727 2728 2729 2730 2731 2732 2733 2734 2735 2736 2737 2738 2739 2740 2741 2742 2743 2744 2745 2746 2747 2748 2749 2750 2751 2752 2753 2754 2755 2756 2757 2758 2759 2760 2761 2762 2763 2764 2765 2766 2767 2768 2769 2770 2771 2772 2773 2774 2775 2776 2777 2778 2779 2780 2781 2782 2783 2784 2785 2786 2787 2788 2789 2790 2791 2792 2793 2794 2795 2796 2797 2798 2799 2800 2801 2802 2803 2804 2805 2806 2807 2808 2809 2810 2811 2812 2813 2814 2815 2816 2817 2

Figure 77





Figure 78



Data Objects

✓ The ApplicationMediatorImpl will forward the refresh (default)

FIGURE
79

```
for each: ApplicationMediator -> refresh(data)
for each: ViewController -> refresh(data);
```

✓ The ViewController will update the GUI

FIGURE
80

```
public void refresh(Object data) {
    //this example uses a keyvalue pair data model
    if (data == null) return;
    else refresh((KeyValue) data);
}

public void refresh (KeyValue data) {
    nameField.setText(data.get("CustomerName"));
    idField.setText(data.get("CustomerId"));
    repaint(); //if necessary
}
```

Data Objects

✓ How can we add a new data model (i.e. real objects)?

FIGURE

81


```
public void refresh(Object data) {  
    if (data == null) return;  
    else if (data instanceof Vector) {  
        refresh((Vector) data);  
    }  
    else if (data instanceof KeyValue) {  
        refresh((KeyValue) data);  
    }  
}
```


FIGURE

82

```
public void refresh(Vector data) {  
    //I know what they are  
    Customer c = (Customer) data.elementAt(0);  
    ID id = (ID) data.elementAt(1);  
    nameField.setText(c.getName());  
    idField.setText(id.toString());  
    repaint(); //if necessary  
}
```

More on data








Figure 85

FIGURE 86

Handling AWTEvents




FIGURE 87

Applying ValidationRules




FIGURE 88

fireViewEvent




Figure 89
Application Manager




Figure 91
Application Manager




Figure 92
Application Manager




Figure 93
Application Manager




Figure 90
Application Manager





Figure 94
Application Manager



05430361 302929



Year	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100
1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	

FIGURE 96

refresh(Object data) in
ApplicationMediator




FIGURE 97

Refresh (Object data) in
ViewController




FIGURE 98





Figure 99






FIGURE 101





FIGURE 102

Encoding Application Mediators

- S1: (VE.source==vc1 && VE.major==A && VE.minor==B) ==>
 (RE.major=C RE.minor=D RE.data=VE.data RE.fireS)
 if event source is vc1 with A,B as major/minor then
 fire sync request with C,D major/minor and use data from event)
- S2: (VE.source==vc4 && VE.major==5) ==> (TE.major=3 TE.fire)
 if event source is vc4 with 5 as major then
 fire top event with major 3
- S3: (Refresh) ==> (VC.i.refresh(Refresh.data))
 if refresh(data) occurs, then refresh all view controllers with the
 same data, but not the other application mediators
- S4: (VE.source==vca) ==> (RE.major="set" RE.fireA) &&
 (PE.major=PE.ADD PE.source=vcB PE.fire) && (VC.vcB.refresh(RE.data))
 if event source is vca, then fire async request, then fire placement
 event, then refresh the newly placed view controller with the data
 returned with the request



Process actions for each ViewEvent

FIGURE 104




Figure 105





Figure 106




```

/**
 * Default method comment.
 *
 * <P>PRE:
 * <P>POST:
 *
 * @return Parameter not modified
 * @return java.lang.Object
 * @param index int
 */
public final Object getData(int Index) {
    Object retVal = null;

    if ((data != null) && (index < data.length)) {
        retVal = data[index];
    }

    return retVal;
}

/**
 * Default method comment.
 *
 * <P>PRE:
 * <P>POST:
 *
 * @return Parameter not modified
 * @param in ObjectInput
 */
public void readExternal(ObjectInput in)
    throws ClassNotFoundException, IOException {

    setData((Object[])in.readObject());
}

/**
 * Default method comment.
 *
 * <P>PRE:
 * <P>POST:
 *
 * @return Parameter not modified
 * @param dataArray java.lang.Object[]
 */
public final void setData(Object[] dataArray) {
    data = dataArray;
}

```

Figure 107

10700
pg 2

Figure 107

```
/**
 * Default method comment.
 *
 * <P>PRE:
 * <P>POST:
 *
 * @return Parameter not modified
 * @param index int
 * @param dataElement java.lang.Object
 */
public final void setData(int index, Object dataElement) {
    if ((data != null) && (index < data.length)) {
        data[index] = dataElement;
    }
}

/**
 * Default method comment.
 *
 * <P>PRE:
 * <P>POST:
 *
 * @return Parameter not modified
 * @param out ObjectOutputStream
 */
public void writeExternal(ObjectOutput out) throws IOException {
    out.writeObject(getData());
}
}
```

10700

pg 3

Figure 108

```
package com.ibm.jtcx.serialization;

import java.io.Externalizable;
import java.io.IOException;
import java.io.ObjectInput;
import java.io.ObjectOutput;
import java.math.BigDecimal;
import java.math.BigInteger;
import java.util.Date;
import java.util.Enumeration;
import java.util.GregorianCalendar;
import java.util.Hashtable;
import java.util.SimpleTimeZone;
import java.util.TimeZone;
import java.util.Vector;
/**
 * Base class of data objects that require small serialization. The
 * attributes of the data object are stored in an array and the elements
 * of the array are written individually.
 *
 * <P>INVARIANT:
 */
public class BaseDataS extends BaseData implements Externalizable {
/**
 * Default constructor.
 */
public BaseDataS() {
    super();
}
/**
 * Creates a new <code>BaseDataS</code> object with a data array of
 * size <code>count</code>.
 *
 * @param count the size of the data array containing the attributes
 */
public BaseDataS(int count) {
    super(count);
}
```

10800
pg 1

10800 pg 1

```

}
/**
 * Reads the array of data elements from the stream. The responsibility
 * of reading the individual element is left to the
 * <code>BaseSerializer</code> via <code>readObject()</code>.
 *
 * @param in the input stream that contains the serialized object
 * @exception ClassNotFoundException thrown if
 * <code>BaseSerializer</code> fails to read the object from the stream
 * @exception IOException thrown if
 * <code>BaseSerializer</code> fails to read the object from the stream
 * @see BaseSerializer#readObject
 */
public void readExternal(ObjectInput in)
    throws ClassNotFoundException, IOException {

    int size = in.readShort();

    if (size == -1) {
        setData(null);
    } else {
        Object[] array = new Object[size];

        for (int i = 0; i < size; i++) {
            array[i] = BaseSerializer.getInstance().readObject(in);
        }

        setData(array);
    }
}

/**
 * Writes the array of data elements. The responsibility of writing the
 * data elements is left to <code>BaseSerializer</code> via
 * <code>writeObject()</code>.
 *
 * @param out the output stream to which the data elements will be
 * written
 */
public void writeExternal(ObjectOutput out) throws IOException {
    Object[] array = getData();

    if (array == null) {
        out.writeShort(-1);
    } else {
        out.writeShort(array.length);

        for (int i = 0; i < array.length; i++) {
            BaseSerializer.getInstance().writeObject(out, array[i]);
        }
    }
}
}

```

Figure 108

10800
pg 2

10800 pg 2

Figure 109

10900

pg 1

```
package com.ibm.jtcx.serialization;
```

```
import java.io.IOException;
```

```
import java.io.ObjectInput;
```

```
import java.io.ObjectOutput;
```

```
/**
```

- * The interface for those classes that serialize objects to and from
- * a stream. The object that implements this interface should write
- * just the object's attributes, not any other descriptive information
- * about the object. Typically, a `SerializerIF` knows how
- * to serialize a specific class.

```
*/
```

```
public interface SerializerIF {
```

```
/**
```

- * Reads an object from the stream.

```
*
```

- * @return The object that was read.

- * @param in the input stream containing the object

- * @exception java.io.IOException thrown if the stream fails

- * @exception java.lang.ClassNotFoundException thrown if the stream

- * fails

```
*/
```

```
Object readObject(ObjectInput in) throws IOException, ClassNotFoundException;
```

```
/**
```

- * Writes the given object to the stream.

```
*
```

- * @param out the output stream into which the object will be written

- * @param element the object that will be written to the stream

- * @exception java.io.IOException thrown if the stream fails

```
*/
```

```
void writeObject(ObjectOutput out, Object element) throws IOException;
```

```
}
```

```
package com.ibm.jtcx.serialization;
```

```
import java.io.*;
import java.math.BigInteger;
import java.math.BigDecimal;
import java.util.Date;
import java.util.GregorianCalendar;
import java.util.Hashtable;
import java.util.SimpleTimeZone;
import java.util.StringTokenizer;
import java.util.TimeZone;
import java.util.Vector;
```

```
/**
```

```
 * The SerializerIF that is used as the base level
 * serializer. It contains three tables used to serialize objects:
```

```
 * <br><u>
```

```
 *      <li> codeTable: the table containing the serialization code of
 *                      an object based on the name of the class
```

```
 *      <li> nameTable: the table containing the name of the class
 *                      based on the serialization code
```

```
 *      <li> serializationTable: the table containing the serializer of
 *                      of an object based on its serialization code
```

```
 * </u>
```

```
 * <br><br>
```

```
 * BaseSerializer delegates the responsibility of
 * serializing the objects to the SerializerIF associated
 * with that class or to the object itself if it implements
 * Externalizable.
```

```
 */
```

```
public class BaseSerializer implements SerializerIF {
    static private final int NULL_OBJECT = 0;
    static private final int OTHER = 0x00ff;
```

```
    static private final String HASHTABLE_SER = "ClassNameHash.ser";
```

```
    static private final String INI_FILE = "ClassNames.ini";
```

```
    static private Hashtable codeTable = null;
```

```
    static private Hashtable nameTable = null;
```

```
    static private Hashtable serializationTable = null;
```

```
    static private BaseSerializer instance = null;
```

```
    class BigDecimalSerializer implements SerializerIF {
```

```
        public Object readObject(ObjectInput in) throws ClassNotFoundException, IOException {
```

Figure 110

11000

pg 1

SECRET FOR EYES ONLY

Figure 110

11000

pg 2

```
int scale = in.readShort();
int size = in.readShort();
byte[] bytes = new byte[size];
in.readFully(bytes);

BigInteger temp = new BigInteger(bytes);
return new BigDecimal(temp, scale);
}

public void writeObject(ObjectOutput out, Object element) throws IOException {
    BigDecimal bigD = (BigDecimal)element;

    int scale = bigD.scale();
    bigD.setScale(0);
    byte[] bytes = bigD.toBigInteger().toByteArray();
    bigD.setScale(scale);

    out.writeShort(scale);
    out.writeShort(bytes.length);
    out.write(bytes);
}

}

class BigIntegerSerializer implements SerializerIF {
    public Object readObject(ObjectInput in) throws ClassNotFoundException, IOException {

        int size = in.readShort();
        byte[] bytes = new byte[size];
        in.readFully(bytes);

        return new BigInteger(bytes);
    }

    public void writeObject(ObjectOutput out, Object element) throws IOException {
        byte[] bytes = ((BigInteger)element).toByteArray();

        out.writeShort(bytes.length);
        out.write(bytes);
    }
}

class BooleanSerializer implements SerializerIF {
    public Object readObject(ObjectInput in) throws ClassNotFoundException, IOException {

        int value = in.readByte();

        return (value == 1) ? Boolean.TRUE : Boolean.FALSE;
    }

    public void writeObject(ObjectOutput out, Object element) throws IOException {
        out.writeByte(((Boolean)element).booleanValue() ? 1 : 0);
    }
}
}
```

Figure 110

11000

pg 3

```
class ByteSerializer implements SerializerIF {
    public Object readObject(ObjectInput in) throws ClassNotFoundException, IOException {
        byte value = in.readByte();

        return new Byte(value);
    }
    public void writeObject(ObjectOutput out, Object element) throws IOException {
        out.writeByte(((Byte)element).byteValue());
    }
}

class CharacterSerializer implements SerializerIF {
    public Object readObject(ObjectInput in) throws ClassNotFoundException, IOException {
        char value = in.readChar();

        return new Character(value);
    }
    public void writeObject(ObjectOutput out, Object element) throws IOException {
        out.writeChar(((Character)element).charValue());
    }
}

class DateSerializer implements SerializerIF {
    public Object readObject(ObjectInput in) throws ClassNotFoundException, IOException {
        long value = in.readLong();

        return new Date(value);
    }
    public void writeObject(ObjectOutput out, Object element) throws IOException {
        out.writeLong(((Date)element).getTime());
    }
}

class DoubleSerializer implements SerializerIF {
    public Object readObject(ObjectInput in) throws ClassNotFoundException, IOException {
        double value = in.readDouble();

        return new Double(value);
    }
    public void writeObject(ObjectOutput out, Object element) throws IOException {
        out.writeDouble(((Double)element).doubleValue());
    }
}
```

Figure 110

11000

pg 4

```
class FloatSerializer implements SerializerIF {
    public Object readObject(ObjectInput in) throws ClassNotFoundException, IOException {
        float value = in.readFloat();

        return new Float(value);
    }
    public void writeObject(ObjectOutput out, Object element) throws IOException {
        out.writeFloat(((Float)element).floatValue());
    }
}

class GregorianCalendarSerializer implements SerializerIF {
    public Object readObject(ObjectInput in) throws ClassNotFoundException, IOException {
        long time = in.readLong();
        Date date = new Date(time);
        SerializerIF serializer = BaseSerializer.getInstance();
        TimeZone tz = (TimeZone)serializer.readObject(in);

        GregorianCalendar gCalendar = new GregorianCalendar(tz);
        gCalendar.setTime(date);

        return gCalendar;
    }
    public void writeObject(ObjectOutput out, Object element) throws IOException {
        GregorianCalendar temp = (GregorianCalendar)element;

        Date date = temp.getTime();
        TimeZone tz = temp.getTimeZone();

        out.writeLong(date.getTime());
        SerializerIF serializer = BaseSerializer.getInstance();
        serializer.writeObject(out, tz);
    }
}

class IntegerSerializer implements SerializerIF {
    public Object readObject(ObjectInput in) throws ClassNotFoundException, IOException {
        int value = in.readInt();

        return new Integer(value);
    }
    public void writeObject(ObjectOutput out, Object element) throws IOException {
        out.writeInt(((Integer)element).intValue());
    }
}

class LongSerializer implements SerializerIF {
    public Object readObject(ObjectInput in) throws ClassNotFoundException, IOException {
```


Year	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100
1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	

11000
pg 5

Figure 110

11000

pg 6

```
public void writeObject(ObjectOutput out, Object element) throws IOException {
    out.writeShort(((Short)element).shortValue());
}

}

class SimpleTimeZoneSerializer implements SerializerIF {
    public Object readObject(ObjectInput in) throws ClassNotFoundException, IOException {
        int offset = in.readInt();
        SerializerIF serializer = BaseSerializer.getInstance();
        String id = (String)serializer.readObject(in);

        return new SimpleTimeZone(offset, id);
    }

    public void writeObject(ObjectOutput out, Object element) throws IOException {
        SimpleTimeZone temp = (SimpleTimeZone)element;

        out.writeInt(temp.getRawOffset());
        SerializerIF serializer = BaseSerializer.getInstance();
        serializer.writeObject(out, temp.getID());
    }
}

class StringSerializer implements SerializerIF {
    public Object readObject(ObjectInput in) throws ClassNotFoundException, IOException {
        int size = in.readShort();
        byte[] bytes = new byte[size];
        in.readFully(bytes);

        return new String(bytes);
    }

    public void writeObject(ObjectOutput out, Object element) throws IOException {
        byte[] bytes = ((String)element).getBytes();

        out.writeShort(bytes.length);
        out.write(bytes);
    }
}

class VectorSerializer implements SerializerIF {
    public Object readObject(ObjectInput in) throws ClassNotFoundException, IOException {
        int size = in.readShort();

        Vector vector = new Vector(size);
        for (int i = 0; i < size; i++) {
            SerializerIF serializer = BaseSerializer.getInstance();
            vector.addElement(serializer.readObject(in));
        }
    }
}
```

Figure 110

11000

pg 7

```
        return vector;
    }

    public void writeObject(ObjectOutput out, Object element) throws IOException {
        Vector temp = (Vector)element;

        Object[] array = new Object[temp.size()];
        for (int i = 0; i < array.length; i++) {
            array[i] = temp.elementAt(i);
        }

        out.writeShort(array.length);
        for (int i = 0; i < array.length; i++) {
            SerializerIF serializer = BaseSerializer.getInstance();
            serializer.writeObject(out, array[i]);
        }
    }
}

/**
 * Default constructor. The constructor is private because this is a
 * singleton class. When the object is constructed, it initializes its
 * tables.
 */
private BaseSerializer() {
    init();
}

/**
 * Adds the given elements to the three tables.
 *
 * @param className the name of the class
 * @param code the code for the given class
 * @param serializer the object responsible for serializing the given
 * class
 */
private void addDataToTables(String className, Number code, SerializerIF serializer) {
    getCodeTable().put(code, className);
    getNameTable().put(className, code);

    if (serializer != null) {
        getSerializerTable().put(code, serializer);
    }
}
```

Figure 110

11000

pg 8

```
/**
 * Creates the codes and serializer objects for the default serialization
 * classes and adds them to the tables. The tables are then written to
 * a serialized file.
 */
private void createDefaultTables() {
    addDataToTables(BigDecimal.class.getName(), new Byte((byte)1), new
BigDecimalSerializer());
    addDataToTables(BigInteger.class.getName(), new Byte((byte)2), new BigIntegerSerializer());
    addDataToTables(Boolean.class.getName(), new Byte((byte)3), new BooleanSerializer());
    addDataToTables(Byte.class.getName(), new Byte((byte)4), new ByteSerializer());
    addDataToTables(Character.class.getName(), new Byte((byte)5), new CharacterSerializer());
    addDataToTables(Date.class.getName(), new Byte((byte)6), new DateSerializer());
    addDataToTables(Double.class.getName(), new Byte((byte)7), new DoubleSerializer());
    addDataToTables(Float.class.getName(), new Byte((byte)8), new FloatSerializer());
    addDataToTables(GregorianCalendar.class.getName(), new Byte((byte)9), new
GregorianCalendarSerializer());
    addDataToTables(Integer.class.getName(), new Byte((byte)10), new IntegerSerializer());
    addDataToTables(Long.class.getName(), new Byte((byte)11), new LongSerializer());
    addDataToTables(Short.class.getName(), new Byte((byte)12), new ShortSerializer());
    addDataToTables(SimpleTimeZone.class.getName(), new Byte((byte)13), new
SimpleTimeZoneSerializer());
    addDataToTables(String.class.getName(), new Byte((byte)14), new StringSerializer());
    addDataToTables(Vector.class.getName(), new Byte((byte)15), new VectorSerializer());
    addDataToTables(Object.class.getName(), new Byte((byte)16), new ObjectSerializer());

    writeTables();
}
/**
 * Returns an instance of the table of class names, keyed by their code.
 * If the table does not exist, it is created.
 *
 * @return The table of class names.
 */
protected Hashtable getCodeTable() {
    if (codeTable == null) {
        codeTable = new Hashtable();
    }
}
```

```

        return codeTable;
    }
    /**
     * Returns an instance of <code>BaseSerializer</code>.
     *
     * @return An instance of <code>BaseSerializer</code>.
     */
    public static SerializerIF getInstance() {
        if (instance == null) {
            instance = new BaseSerializer();
        }

        return instance;
    }
    /**
     * Returns an instance of the table of codes, keyed by their
     * corresponding class name.
     * If the table does not exist, it is created.
     *
     * @return The table of codes.
     */
    protected Hashtable getNameTable() {
        if (nameTable == null) {
            nameTable = new Hashtable();
        }

        return nameTable;
    }
    /**
     * Returns an instance of the table of serializers, keyed by their
     * corresponding code.
     * If the table does not exist, it is created.
     *
     * @return The table of class names.
     */
    protected Hashtable getSerializerTable() {
        if (serializerTable == null) {
            serializerTable = new Hashtable();
        }

        return serializerTable;
    }
    /**
     * Initializes the hashtable from either a serialized hashtable or from
     * an ini file.
     */

```

Figure 110

11000

pg 9

[illegible]

1.
/ 零半

✱

* **@param className** the name of the class

36

```
Number code = null;
```

}

}

/**

✱

✱

✱

11000

pg 10

```

private String lookupName(Number code) {
    String className = null;

    if (code != null) {
        className = (String)getCodeTable().get(code);
    }

    return className;
}

```

Figure 110

11000

pg 11

```

}
/**
 * Default method comment.
 *
 * <P>PRE:
 * <P>POST:
 *
 * @return Parameter not modified
 * @return com.ibm.jtc.util.SerializerIF
 * @param code int
 */

```

```

private SerializerIF lookupSerializer(Number code) {
    SerializerIF serializer = null;

    if (code != null) {
        serializer = (SerializerIF)getSerializerTable().get(code);
    }

    return serializer;
}

```

```

}
/**
 * Default method comment.
 *
 * <P>PRE:
 * <P>POST:
 *
 * @return Parameter not modified
 * @param inFile java.io.File
 */

```

```

private void readIniFile(File inFile) {
    BufferedReader in = null;

    try {
        in = new BufferedReader(new FileReader(inFile));

        for (String inLine = in.readLine(); inLine != null; inLine = in.readLine()) {
            String trimLine = inLine.trim();

```

11000 pg 11

```

        if ((trimLine.length() > 0) &&
            !trimLine.startsWith("#")) {
            StringTokenizer tokenizer = new StringTokenizer(trimLine);

            String className = tokenizer.nextToken();
            Integer code = new Integer(className.hashCode());
            SerializerIF serializer = null;

            if (tokenizer.hasMoreTokens()) {
                String serializerName = tokenizer.nextToken();

                try {
                    serializer = (SerializerIF)Class.forName(serializerName).newInstance();
                } catch (Exception e) {}
            }

            addDataToTables(className, code, serializer);
        }
    } catch (Exception throwAway) {}
    } finally {
        try {
            in.close();
        } catch (Exception throwAway) {}
    }
}

writeTables();
}
/**
 * Reads the object from the stream by first reading the code for the
 * element then reads the appropriate data for that object.
 *
 * @return The object that was read from the stream.
 * @param in the input stream that contains the object
 */
public Object readObject(ObjectInput in)
    throws ClassNotFoundException, IOException {
    Object retVal = null;
    Number code = null;

    byte baseCode = in.readByte();

```

Figure 110

11000
pg 12

Figure 110

11000
pg 13

```
if (baseCode == NULL_OBJECT) {
    retVal = null;
} else {
    if (baseCode != OTHER) {
        code = new Byte(baseCode);
    } else {
        int secondCode = in.readInt();
        code = new Integer(secondCode);
    }

    SerializerIF serializer = lookupSerializer(code);
    if (serializer != null) {
        retVal = serializer.readObject(in);
    } else {
        String className = lookupName(code);

        try {
            retVal = Class.forName(className).newInstance();

            if (retVal instanceof Externalizable) {
                ((Externalizable)retVal).readExternal(in);
            } else {
                retVal = in.readObject();
            }
        } catch (Exception e) {
        }
    }
}

return retVal;
}

/**
 * Reads the file containing the serialized hashtables of data.
 *
 * @param serializedFile the file containinig the serialized tables
 */
private void readSerializedFile(File serializedFile) {
    ObjectInputStream in = null;
    try {
        in = new ObjectInputStream(new FileInputStream(serializedFile));
        codeTable = (Hashtable)in.readObject();
        nameTable = (Hashtable)in.readObject();
        serializerTable = (Hashtable)in.readObject();
    }
```

```

    } catch (Exception throwAway) {
    } finally {
        try {
            in.close();
        } catch (Exception throwAway) { }

        if ((codeTable == null) ||
            (nameTable == null) ||
            (serializerTable == null)) {

            createDefaultTables();
        }
    }
}

/**
 * Writes the given object to the stream. First, the code representing
 * the type of the object is written, then the data within the object
 * is written.
 *
 * @param out the output stream that will contain the object
 * @param element the data object that will be written
 */
public void writeObject(ObjectOutput out, Object element)
    throws IOException {

    if (element == null) {
        out.writeByte(NULL_OBJECT);
    } else {
        String className = element.getClass().getName();
        Number code = lookupCode(className);

        if (code != null) {
            if (code instanceof Byte) {
                out.writeByte(code.byteValue());
            } else if (code instanceof Integer) {
                out.writeByte(OTHER);
                out.writeInt(code.intValue());
            }
        }

        SerializerIF serializer = lookupSerializer(code);

        if (serializer != null) {
            serializer.writeObject(out, element);
        } else if (element instanceof Externalizable) {
            ((Externalizable)element).writeExternal(out);
        }
    }
}

```

Figure 110

11000

pg 14

Figure 110

11000

pg 15

```
        } else {
            out.writeObject(element);
        }
    } else {
        if (element instanceof Object[]) {
            className = Object[].class.getName();
        } else {
            className = Object.class.getName();
        }

        code = lookupCode(className);
        SerializerIF serializer = lookupSerializer(code);

        out.writeByte(code.byteValue());
        serializer.writeObject(out, element);
    }
}

/**
 * Writes the tables to the file.
 */
private void writeTables() {
    ObjectOutputStream out = null;

    try {
        File serFile = new File(HASHTABLE_SER);
        out = new ObjectOutputStream(new FileOutputStream(serFile));

        out.writeObject(getCodeTable());
        out.writeObject(getNameTable());
        out.writeObject(getSerializerTable());
        out.writeObject(new Date());
    } catch (Exception e) {
    } finally {
        try {
            out.close();
        } catch (Exception e) {}
    }
}
```

Figure 111




Figure 112
Getting/Setting
Permissions




Figure 113
Getting/Setting
Permissions




Figure 114
Getting/Setting
Permissions




Figure 115
Getting/Setting
Permissions




Figure 116
Getting/Setting
Permissions




Figure 117
Getting/Setting
Permissions




Figure 119

Getting/Setting Permissions





Figure 118


Getting/Setting Permissions



Example Pattern

FIGURE 120


- ➔ Interpreted virtual screens
- ➔ Transactional with caching



Example Pattern

FIGURE 121


- ➡ Data models and ViewControllers
- ➡ Transactional



Example Pattern

FIGURE 122

- Live data objects
- Streaming and remote objects
- RequestEvents to turn on/off data objects



Example Pattern

FIGURE 123

→ Non-intrusive Caching, Tracing or Logging

